

The image is a large, symmetrical, abstract graphic composed of the letters 'S' and 'Y' arranged in a grid-like pattern. The overall shape is a stylized 'Y' or a complex letterform. The top part is a wide horizontal bar made of 'S's, with 'Y's forming a central vertical stem. The sides of the 'Y' are also formed by 'S's and 'Y's, creating a sense of depth and structure. The letters are arranged in a way that they interlock and form a cohesive, geometric design. The color is a dark, muted green on a light background.

[illegible]

(1) 487
(1) 1734

Macros for Loadable Services
REGION 2 OF SYS. SERV. VECTOR DEFINITIONS


```
00000001 0000 1 RMSSWITCH=1 ;GENERATE RMS SERVICE CASE BRANCH TABLE
0000 1 .NLIST CND
0000 14 .TITLE SYSSRMS_VECTOR - RMS SERVICE VECTOR DEFINITIONS
0000 19 .IDENT 'V04-000'
0000 20
0000 21
0000 22
0000 23
0000 24
0000 25
0000 26
0000 27
0000 28
0000 29
0000 30
0000 31
0000 32
0000 33
0000 34
0000 35
0000 36
0000 37
0000 38
0000 39
0000 40
0000 41
0000 42
0000 43
0000 44
0000 45
0000 46
0000 47
0000 48
0000 49
0000 50
0000 51
0000 52
0000 53
0000 54
0000 55
0000 56
0000 57
0000 58
0000 59
0000 60
0000 61
0000 62
0000 63
0000 64
0000 65
0000 66
0000 67
0000 68
0000 69
0000 70
0000 71
0000 72
```

COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
ALL RIGHTS RESERVED.

THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
TRANSFERRED.

THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
CORPORATION.

DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.

D. N. CUTLER 22-JUN-76

MODIFIED BY:

V03-041 LJK0287 Lawrence J. Kenah 2-Jun-1984
Add R5 to entry mask for \$CANEXH system service.

V03-040 LMP0239 L. Mark Pilant, 23-Apr-1984 9:21
Change \$CHKPRO from an exec mode service to a kernel mode
service. This was made necessary by the \$CHKPRO (internal
entry point) interface change.

V03-039 MMD0250 Meg Dumont, 27-Feb-1984 17:49
Add support for \$MTACCESS installation specific accessibility
routine

V03-038 DAS0001 David Solomon 20-Feb-1984
Implement new design for RMS echo SYSS\$INPUT to SYSS\$OUTPUT
(vs V03-019). Echo is now performed by a caller's mode AST
routine declared in RMS\RMSEXAMS. Change INCB/DECB of FAB/RAB
busy bit to BISB/BICB, now that we have room.

V03-037 SSA0004 Stan Amway 28-Dec-1983
For \$SETPFM, changed number of parameters from 1 to 4
and changed entry mask to save R2-R11.

V03-036 TMK0002 Todd M. Katz 19-Nov-1983
The entry point for \$ASCTOID can no longer be reached as a

0000	73	:	branch destination from the executive mode dispatcher.
0000	74	:	A temporary entry point (EXESASCTOID) has been placed within
0000	75	:	this module, and a JMP is made from it to the real system
0000	76	:	service entry point (EXESASCTOID).
0000	77	:	
0000	78	:	Also, change the entry mask for SYSSTRNLOG, so that R8 is
0000	79	:	now saved.
0000	80	:	
0000	81	:	V03-035 TMK0001 Todd M. Katz 22-Oct-1983
0000	82	:	The entry points for \$FINISH_RDB and \$IDTOASC can no
0000	83	:	longer be reached as branch destinations from the executive
0000	84	:	mode dispatcher. Temporary entry points (EXESFINISH_RDB and
0000	85	:	EXESIDTOASC) have been placed within this module, and from
0000	86	:	each a JMP is made to the real system service entry points
0000	87	:	(EXESFINISH_RDB and EXESIDTOASC).
0000	88	:	
0000	89	:	V03-034 PRB0254 Paul Beck 15-Sep-1983 14:49
0000	90	:	(1) Correct the way synchronous CJF services are defined.
0000	91	:	(2) Define loadable RUF services.
0000	92	:	
0000	93	:	V03-033 WMC0029 Wayne Cardoza 31-Aug-1983
0000	94	:	Loadable services should not be unconditionally inhibited.
0000	95	:	Add an alternate CHMx argument to LDBSRV.
0000	96	:	
0000	97	:	V03-032 DWT0125 David W. Thiel 22-Aug-1983
0000	98	:	Remove CHECKARGLIST and calls to same.
0000	99	:	
0000	100	:	V03-031 MKL0167 Mary Kay Lyons 19-Aug-1983
0000	101	:	Generate loadable service vector for CJF\$GETCJI.
0000	102	:	
0000	103	:	V03-030 KBT0578 Keith B. Thompson 8-Aug-1983
0000	104	:	Add parameter to \$FILESCAN
0000	105	:	
0000	106	:	V03-029 RAS0178 Ron Schaefer 29-Jul-1983
0000	107	:	Add code to detect the AST/non-AST RMS FAB/RAB race
0000	108	:	condition where an RMS operation is initiated while
0000	109	:	the user FAB/RAB is still waiting for completion of
0000	110	:	previous operation.
0000	111	:	
0000	112	:	V03-028 WMC0028 Wayne Cardoza 29-Jun-1983
0000	113	:	Add CJF services.
0000	114	:	
0000	115	:	V03-027 WMC0027 Wayne Cardoza 23-Jun-1983
0000	116	:	Make old logical name services "all mode".
0000	117	:	Changes to image activator vectors.
0000	118	:	
0000	119	:	V03-026 JWH0222 Jeffrey W. Horn 2-May-1983
0000	120	:	Add LDBSRV macro for vector definitions of loadable
0000	121	:	services.
0000	122	:	
0000	123	:	V03-025 DMW4035 DMWalp 26-May-1983
0000	124	:	Intergate new logical name structures.
0000	125	:	
0000	126	:	V03-024 LMP0109 L. Mark Pilant, 28-Apr-1983 15:53
0000	127	:	Make \$CHKPRO an EXEC mode system service to allow examination
0000	128	:	of various system data structures.
0000	129	:	

0000	130	:	V03-024	RAS0147	Ron Schaefer	28-APR-1983	
0000	131	:		Add \$FILESCAN.	Add R8 and R9 to \$SETPRN register mask.		
0000	132	:					
0000	133	:	V03-023	JLV0244	Jake VanNoy	27-APR-1983	
0000	134	:		Add \$BRKTHRUW.	Change \$BRDCST to all mode service.		
0000	135	:		\$BRDCST	now uses \$BRKTHRU to do real work.		
0000	136	:					
0000	137	:	V03-022	LMP0099	L. Mark Pilant,	13-Apr-1983	19:15
0000	138	:		Add the \$CHKPRO	system service.		
0000	139	:					
0000	140	:	V03-021	ACG0319	Andrew C. Goldstein,	21-Mar-1983	13:51
0000	141	:		Add \$GRANTID	and \$REVOKID services		
0000	142	:					
0000	143	:	V03-020	JLV0234	Jake VanNoy	1-MAR-1983	
0000	144	:		Add \$BRKTHRU	service.		
0000	145	:					
0000	146	:	V03-019	RAS0120	Ron Schaefer	25-Feb-1983	
0000	147	:		Add support to echo	SYSS\$INPUT to SYSS\$OUTPUT.		
0000	148	:		This involves examining	the return code from RMS for \$GET;		
0000	149	:		if the special status	RMS\$ ECHO (not returned to users)		
0000	150	:		is found, then create	a RAB on the caller's stack and		
0000	151	:		execute a \$PUT	operation to echo the line.		
0000	152	:		A certain amount of	RMS synchronization code was		
0000	153	:		shuffled around in	order to make room for this.		
0000	154	:					
0000	155	:	V03-018	ACG0317	Andrew C. Goldstein,	22-Feb-1983	15:16
0000	156	:		Fix off-by-one in	kernel arg vector		
0000	157	:					
0000	158	:	V03-017	RSH0004	R. Scott Hanna	10-Feb-1983	
0000	159	:		Added \$ASCTOID,	\$FINISH_RDB, and \$IDTOASC to system service list		
0000	160	:					
0000	161	:	V03-016	RNG0016	Rod N. Gamache	1-Feb-1983	
0000	162	:		Added \$GETLKI	to system service list		
0000	163	:					
0000	164	:	V03-015	WMC0015	Wayne Cardoza	12-Jan-1983	
0000	165	:		Put back accidentally	deleted space holder for RMS synchronization.		
0000	166	:					
0000	167	:	V03-014	DMW4023	DMWalp	7-Jan-1983	
0000	168	:		Added \$CRELNT,	\$CRELNM, \$DELLNM and \$TRNLNM		
0000	169	:					
0000	170	:	V03-013	KDM0033	Kathleen D. Morse	13-Dec-1982	
0000	171	:		Correct usage of	an interlocked instruction to flush		
0000	172	:		the hardware cache	queue.		
0000	173	:					
0000	174	:	V03-012	ROW0146	Ralph O. Weber	6-DEC-1982	
0000	175	:		Insert routine header	comments for INHEXCP, CHECKARGLIST,		
0000	176	:		and EXE\$MODKRN LX	(MPSS\$MODKRN LX). Move things around so		
0000	177	:		that EXE\$MODKRN LX	(MPSS\$MODKRN LX) header comments are near		
0000	178	:		EXE\$MODKRN LX	(MPSS\$MODKRN LX) and ASTEXIT comments are near		
0000	179	:		ASTEXIT. Make basic	kernal-mode .PSECT definition for Y\$MODK		
0000	180	:		or MP\$MOD1	immediately after executive mode code so that new		
0000	181	:		code can be inserted	in a way that preserves routine headers,		
0000	182	:		conditional assembly,	and .PSECT definitions. Backout ROW145,		
0000	183	:		and in its place,	correct conditional assembly of BGEQU 10\$		
0000	184	:		after ACCVID_RET	so that it is assembled only for MPCMOD and		
0000	185	:		so that it is located	before ACCVID_RET. Change PCB address		
0000	186	:		lookup at KERDSP	in MPCMOD to use CTL\$GL_PCB so that it works		

```

0000 187 : correctly regardless of which processor executes it.
0000 188 :
0000 189 :
0000 190 : V03-011 ROW0145 Ralph D. Weber 29-NOV-1982
0000 191 : Move EX$EXCPTN (and MP$EXCPTN) to before ASTEXIT (or
0000 192 : MP$ASTEXIT) in an attempt to make branch destinations in
0000 193 : EX$CMODKRNL reach.
0000 194 :
0000 195 : V03-010 KDM0030 Kathleen D. Morse 18-Nov-1982
0000 196 : Add logic to MPCMOD that allows the primary to execute
0000 197 : secondary-specific code, without turning into a secondary.
0000 198 :
0000 199 : V03-009 MLJ0099 Martin L. Jack, 20-Oct-1982 19:42
0000 200 : Complete V03-002 by correcting mode and argument count of
0000 201 : $SNDJBC and removing temporary stubs.
0000 202 :
0000 203 : V03-008 RIH0001 Richard I. Hustvedt 1-Jun-1982
0000 204 : Correct handling of AST queue by secondary processor to
0000 205 : avoid losing some AST notifications by incorrectly computing
0000 206 : PHD$B_ASTLVL.
0000 207 :
0000 208 : V03-007 KDM0018 Kathleen D. Morse 30-Sep-1982
0000 209 : Add MPSWITCH logic to create a kernel system service
0000 210 : dispatcher for the secondary processor of an 11/782.
0000 211 :
0000 212 : V03-006 STJ3028 Steven T. Jeffreys 26-Sep-1982
0000 213 : Added $ERAPAT system service vector.
0000 214 :
0000 215 : V03-005 DWT0058 David Thiel 11-Aug-1982
0000 216 : Eliminate use of R2 while waiting for service
0000 217 : completion.
0000 218 :
0000 219 : V03-004 JWH0001 Jeffrey W. Horn 26-Jul-1982
0000 220 : Add new RMS service, RMSRUHNDLR, an un-documented service
0000 221 : which acts as the Recovery Unit handler for RMS.
0000 222 :
0000 223 : V03-003 PHL0102 Peter H. Lipman 16-Jul-1982
0000 224 : Fix new SYNCH logic to always return SS$_NORMAL,
0000 225 : not access IOSB if error from service, and return
0000 226 : error status from $SETEF if event flag cluster went away
0000 227 :
0000 228 : V03-002 PHL0101 Peter H. Lipman 17-Jun-1982
0000 229 : Add $SYNCH system service and fix $QIOW and $ENQW to use the
0000 230 : new code for waiting for the combination of EFN and IOSB
0000 231 :
0000 232 : Improve readability of conditionals.
0000 233 :
0000 234 : Add $GETDVIW, $GETJPIW, $GETSYIW, $SNDJBC, $SNDJBCW, and
0000 235 : $UPDSECW. All the waiting versions use common code.
0000 236 :
0000 237 :
0000 238 : CHANGE MODE SYSTEM SERVICE DISPATCHER
0000 239 :
0000 240 : MACRO LIBRARY CALLS
0000 241 :
0000 242 :
0000 243 : $ACBDEF ;DEFINE AST CONTROL BLOCK OFFSETS

```



```
0000 244 $CHFDEF ;DEFINE CONDITION HANDLING OFFSETS
0000 245 $ENQDEF ;DEFINE ENQ SYSTEM SERVICE ARGS
0000 246 $GETDVIDEF ;DEFINE GETDVI SYSTEM SERVICE ARGS
0000 247 $GETJPIDEF ;DEFINE GETJPI SYSTEM SERVICE ARGS
0000 248 $GETLKIDEF ;DEFINE GETLKI SYSTEM SERVICE ARGS
0000 249 $GETSYIDEF ;DEFINE GETSYI SYSTEM SERVICE ARGS
0000 250 $IPLDEF ;DEFINE INTERRUPT PRIORITY LEVELS
0000 254 $PCBDEF ;DEFINE PCB OFFSETS
0000 255 $PHDDEF ;DEFINE PHD OFFSETS
0000 256 $PRDEF ;DEFINE PROCESSOR REGISTERS
0000 257 $PSLDEF ;DEFINE PROCESSOR STATUS FIELDS
0000 258 $RABDEF ;DEFINE RMS RAB FIELDS
0000 259 $RPBDEF ;DEFINE REBOOT PARAMETER BLOCK
0000 260 $QIODEF ;DEFINE QIO SYSTEM SERVICE ARGS
0000 261 $SGNDEF ;DEFINE SYSGEN PARAMETERS
0000 262 $$NDJBCDEF ;DEFINE SNDJBC SYSTEM SERVICE ARGS
0000 263 $$$DEF ;DEFINE SYSTEM STATUS VALUES
0000 264 $$SYNCHDEF ;DEFINE SYNCH SYSTEM SERVICE ARGS
0000 265 $UPDSECDDEF ;DEFINE UPDATE SECTION SYS SRV ARGS
0000 266 :
0000 267 : LOCAL EQUATES
0000 268 :
00000001 0000 269 CAT0 = 120
00000080 0000 270 CAT7 = 127
00000081 0000 271 DEF_MASK = CAT0!CAT7 ;INHIBIT FOR 'ALL' AND 'NOT EXIT'
00000080 0000 272 EXC_MASK = CAT7 ;INHIBIT ONLY FOR 'ALL' CASE
0000 273 :
0000 274 : LOCAL MACROS
0000 275 :
0000 276 GSYSSRV - GENERATE SYSTEM SERVICE ENTRY VECTOR
0000 277
0000 278 GSYSSRV SRVNAME,MODE,NARG,REGISTERS,MASK,NOSYNC
0000 279
0000 280 WHERE:
0000 281 SRVNAME - SERVICE NAME LESS ANY PREFIX (SYSS$,EXE$,RMS$$)
0000 282 MODE - MODE DESIGNATOR FOR SERVICE (K,E,ALL,R)
0000 283 NARG - REQUIRED NUMBER OF ARGUMENTS
0000 284 REGISTERS - REGISTER SAVE LIST
0000 285 MASK - SERVICE INHIBIT MASK(BIT SET IN CAT INHIBITS)
0000 286 NOSYNC - NON-ZERO IF RMS SYNCHRONIZATION CODE NOT TO BE INCLUDED
0000 287 :
0000 288
0000 289 .MACRO GSYSSRV,SRVNAME,MODE,NARG,REGS,MASK=DEF_MASK,NOSYNC
0000 290 .IF NDF,RMSSWITCH
0000 291 .IF DF,LIBSWITCH
0000 292 .PSECT $$$0000,QUAD
0000 293 .IFF
0000 294 .PSECT $$$0000,QUAD
0000 295 .ENDC
0000 296 .ALIGN QUAD
0000 297 .IF DF LIBSWITCH
0000 298 SYSS$SRVNAME::
0000 299 .IFF
0000 300 .IF NDF,MPSWITCH
0000 301 .WORD ^M<REGS>
0000 302 SRVNAME MASK = ^M<REGS>
0000 303 .IFTF ;MPSWITCH
```



```
0000 304 .IF B NOSYNC
0000 305 SRV'MODE SRVNAME,NARG,MASK
0000 306 .IFF
0000 307 SRV'MODE SRVNAME,NARG,MASK,NOSYNC
0000 308 .ENDC
0000 309 .ENDC ;MPSWITCH
0000 310 .IFT
0000 311 .BLKL 2
0000 312 .ENDC
0000 313 .IFF
0000 314 SRV'MODE SRVNAME,NARG,MASK
0000 315 .ENDC
0000 316 .ENDM GSYSSRV
0000 317
0000 318 :
0000 319 :
0000 320 :
0000 321 :
0000 322 :
0000 323 :
0000 324 :
0000 325 :
0000 326 :
0000 327 :
0000 328 :
0000 329 :
0000 330 .MACRO GCOMPSRVB,SRVNAME,REGMSK,PREFIX=SYSS
0000 331 .IF NDF,MPSWITCH
0000 332 .IF NDF,RMSSWITCH
0000 333 .IF DF,LIBSWITCH
0000 334 .PSECT $$$0000,QUAD
0000 335 .IFF
0000 336 .PSECT $$$000,QUAD
0000 337 .ENDC
0000 338 .ALIGN QUAD
0000 339 .IF DF LIBSWITCH
0000 340 .IIF NOT_BLANK, <SRVNAME>,-
0000 341 'PREFIX' SRVNAME::
0000 342 .IFF
0000 343 .ENABL LSB
0000 344 COMPSTR=
0000 345 .IIF NOT_BLANK, <REGMSK>,-
0000 346 <REGMSK>
0000 347 .ENDC
0000 348 .ENDC
0000 349 .ENDC ;MPSWITCH
0000 350 .ENDM GCOMPSRVB
0000 351
0000 352 :
0000 353 :
0000 354 :
0000 355 :
0000 356 :
0000 357 :
0000 358 :
0000 359 :
0000 360 :
```

GCOMPSRVB - GENERATE COMPOSITE SYSTEM SERVICE ENTRY VECTOR BEGIN

GCOMPSRVB SRVNAME,REGISTER_MASK[,PREFIX]

WHERE:

SRVNAME - SERVICE NAME LESS ANY PREFIX (SYSS\$, EXES\$)

REGISTER_MASK - SYMBOLIC REGISTER MASK, E.G QIO MASK

PREFIX - IF SUPPLIED, THE PREFIX FOR THE SERVICE NAME.
IF OMITTED, "SYSS\$" IS ASSUMED.

GCOMPSRVB,SRVNAME,REGMSK,PREFIX=SYSS

NDF,MPSWITCH

NDF,RMSSWITCH

DF,LIBSWITCH

\$\$\$0000,QUAD

\$\$\$000,QUAD

QUAD

LIBSWITCH

NOT_BLANK, <SRVNAME>,-

'PREFIX' SRVNAME::

LSB

COMPSTR=

NOT_BLANK, <REGMSK>,-

<REGMSK>

MPSWITCH

GCOMPSRVB

GCOMPSRVB - GENERATE COMPOSITE SYSTEM SERVICE ENTRY VECTOR END

GCOMPSRVB QUADWORDS

WHERE:

QUADWORDS - NUMBER OF QUADWORDS TO RESERVE FOR VECTOR

```

0000 361      .MACRO  GCOMPSRVE,QUADS
0000 362      .IF     NDF,MPSWITCH
0000 363      .IF     NDF,RMSSWITCH
0000 364      .IF     DF,LIBSWITCH
0000 365      .BLKQ   QUADS
0000 366      .IFF
0000 367  COMPSIZE=-COMPSTRT
0000 368      .IF     GE,QUADS*8-COMPSIZE
0000 369      .BLKB   QUADS*8-COMPSIZE
0000 370      .IFF
0000 371      .ERROR          ; VECTOR EXCEEDS ALLOCATED SIZE ;
0000 372      .ENDC
0000 373      .DSABL   LSB
0000 374      .ENDC
0000 375      .ENDC
0000 376      .ENDC      ;MPSWITCH
0000 377      .ENDM      GCOMPSRVE
0000 378
0000 379
0000 380  :
0000 381  :      SRVK - GENERATE ENTRY FOR KERNEL MODE SERVICE
0000 382  :
0000 383  :      SRVK      SRVNAME,NARG,MASK
0000 384  :
0000 385
0000 386      .MACRO  SRVK,SRVNAME,NARG,MASK
0000 387      .IF     NDF,RMSSWITCH
0000 388      .IF     DF,MPSWITCH
0000 389  CMK$C_'SRVNAME==KCASCTR
0000 390      .IFF      :MPSWITCH DEFINED
0000 391  CMK$C_'SRVNAME=KCASCTR
0000 392      CHMK      #SRVNAME
0000 393      RET
0000 394      .PSECT   Y$CMODKN,BYTE
0000 395      .=KCASCTR
0000 396      ASSUME   NARG LE 127
0000 397      .BYTE    NARG
0000 398      .PSECT   Y$CMODKX,BYTE
0000 399      .=KCASCTR
0000 400      .BYTE    MASK
0000 401      .PSECT   Y$CMODK,BYTE
0000 402      .SIGNED_WORD  EXES'SRVNAME-KCASE+2
0000 403      .IFTF    ;MPSWITCH
0000 404  SRVNAME=KCASCTR
0000 405  KCASCTR=KCASCTR+1
0000 406      .ENDC      ;MPSWITCH
0000 407      .ENDC
0000 408      .ENDM      SRVK
0000 409
0000 410  :
0000 411  :      SRVE - GENERATE ENTRY FOR EXECUTIVE MODE SERVICE
0000 412  :
0000 413  :
0000 414      .MACRO  SRVE,SRVNAME,NARG,MASK
0000 415      .IF     NDF,MPSWITCH
0000 416      .IF     NDF,RMSSWITCH
0000 417  CMES$C_'SRVNAME=ECASCTR

```



```
0000 418      CHME      #SRVNAME
0000 419      RET
0000 420      .PSECT   Y$CMODEN,BYTE
0000 421      .=ECASCTR
0000 422      ASSUME   NARG LE 127
0000 423      .BYTE    NARG
0000 424      .PSECT   Y$CMODEX,BYTE
0000 425      .=ECASCTR
0000 426      .BYTE    MASK
0000 427      .PSECT   Y$CMODE,BYTE
0000 428      .SIGNED_WORD  EXES'SRVNAME-ECASE+2
0000 429      .ENDC
0000 430      SRVNAME=ECASCTR
0000 431      ECASCTR=ECASCTR+1
0000 432      .ENDC      ;MPSWITCH
0000 433      .ENDM      SRVE
0000 434      :
0000 435      :
0000 436      :      MACROS FOR GENERATING RMS SYSTEM VECTORS
0000 437      :
0000 438      .MACRO   RMSSRV   SRVNAME NARG=1,REGS=<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>,-
0000 439                      MASK,NOSYNC=0
0000 440      GSYSSRV   SRVNAME,R,NARG,<REGS>,MASK,NOSYNC
0000 441      .ENDM      RMSSRV
0000 442      :
0000 443      :      SRVR - GENERATE ENTRY FOR RMS SERVICE (EXEC MODE)
0000 444      :
0000 445      .MACRO   SRVR      SRVNAME,NARG,MASK,NOSYNC
0000 446      .IF      NDF,MPSWITCH
0000 447      .IF      NDF,RMSSWITCH
0000 448      CMESC_ 'SRVNAME=RCASCTR
0000 449      CHME      #SRVNAME
0000 450      .IF EQ NOSYNC
0000 451      .IIF GT <.+2-RMSSYNC>-127,-
0000 452      RMSSYNC=RMSWBR                                     ;RESET BRANCH DESTINATION
0000 453      RMSWBR=.
0000 454      BRB      RMSSYNC
0000 455      .IFF
0000 456      RET
0000 457      .ENDC
0000 458      .PSECT   Y$CMODEN,BYTE
0000 459      .=RCASCTR
0000 460      ASSUME   NARG LE 127
0000 461      .BYTE    NARG
0000 462      .PSECT   Y$CMODEX,BYTE
0000 463      .=RCASCTR
0000 464      .BYTE    MASK
0000 465      .IFF
0000 466      .PSECT   $$$RMSVEC,BYTE,NOWRT
0000 467      .SIGNED_WORD  RMSS'SRVNAME-RCASE+2
0000 468      .ENDC
0000 469      SRVNAME=RCASCTR
0000 470      RCASCTR=RCASCTR+1
0000 471      .ENDC      ;MPSWITCH
0000 472      .ENDM      SRVR
0000 473      :
0000 474      :
```

```
0000 475 :  
0000 476 :  
0000 477 :  
0000 478  
0000 479 .MACRO SRVALL,SRVNAME,NARG,MASK  
0000 480 .IF NDF,MPSWITCH  
0000 481 .IF NDF,RMSWITCH  
0000 482 JMP @EXES,SRVNAME+2  
0000 483 .ENDC  
0000 484 .ENDC ;MPSWITCH  
0000 485 .ENDM SRVALL
```



```
0000 487 .SBTTL Macros for Loadable Services
0000 488
0000 489 :
0000 490 LDBSRV - Generate Loadable Service Vector
0000 491
0000 492 LDBSRV PREFIX,SRVNAME,MODE,REGS,SYN_EFN,SYN_IOSB,ALT_CHMX
0000 493
0000 494 Where:
0000 495 PREFIX - Prefix for system service vector entry point name
0000 496 SRVNAME - Service name less any prefix (SYSS,CJFS, etc.)
0000 497 MODE - Mode designator for service (K,E,ALL)
0000 498 REGS - Register save list
0000 499 SYN_EFN - Event flag argument number for $SYNCH
0000 500 SYN_IOSB - IOSB argument number for $SYNCH
0000 501 ALT_CHMX - Use same CHMX number as this service
0000 502 :
0000 503
0000 504 .MACRO LDBSRV,PREFIX,SRVNAME,MODE,REGS,SYN_EFN,SYN_IOSB,ALT_CHMX
0000 505 .IF NDF,RMSSWITCH
0000 506 .IF NDF,MPSWITCH
0000 507 .IF DF,LIBSWITCH
0000 508 .PSECT $$$0000,QUAD
0000 509 .ALIGN QUAD
0000 510 PREFIX''SRVNAME::
0000 511 .IF BLANK SYN_EFN
0000 512 .BLKL 2
0000 513 .IFF
0000 514 .BLKL 4
0000 515 .ENDC
0000 516 .IFF
0000 517 .PSECT $$$000,QUAD
0000 518 .ALIGN QUAD
0000 519 .WORD "M<REGS>"
0000 520 SRVNAME' MASK = "M<REGS>"
0000 521 LVEC_'MODE PREFIX,SRVNAME,SYN_EFN,SYN_IOSB,ALT_CHMX
0000 522 .ENDC
0000 523 .ENDC ; MPSWITCH
0000 524 .ENDC ; RMSSWITCH
0000 525 .ENDM LDBSRV
0000 526
0000 527 :
0000 528 LVEC_K - Kernel Mode Loadable System Service Vector
0000 529
0000 530 LVEC_K PREFIX,SERVICE,EFN,IOSB
0000 531 :
0000 532
0000 533 .MACRO LVEC_K,PREFIX,SERVICE,EFN,IOSB,ALT_CHMX
0000 534 .IF BLANK ALT_CHMX
0000 535 CMKSC_'SERVICE = PREFIX'KCASCTR
0000 536 .IFF
0000 537 CMKSC_'SERVICE = ALT_CHMX
0000 538 .ENDC
0000 539 CMK #SERVICE
0000 540 .IF NOT BLANK EFN
0000 541 PUSHL #EFN
0000 542 PUSHL #IOSB
0000 543 JMP @#EXE$LDB_SYNCH
```

```
0000 544 .IFF
0000 545 RET
0000 546 .ENDC
0000 547 .IF BLANK ALT_CHMK
0000 548 SERVICE = PREFIX'KCASCTR
0000 549 PREFIX'KCASCTR = PREFIX'KCASCTR + 1
0000 550 .IFF
0000 551 SERVICE = ALT_CHMK
0000 552 .ENDC
0000 553 .ENDM LVEC_K
0000 554
0000 555
0000 556 LVEC_E - Exec Mode Loadable System Service Vector
0000 557
0000 558 LVEC_E PREFIX,SERVICE,EFN,IOSB
0000 559
0000 560
0000 561 .MACRO LVEC_E,PREFIX,SERVICE,EFN,IOSB,ALT_CHME
0000 562 .IF BLANK ALT_CHME
0000 563 CMESC_'SERVICE = PREFIX'ECASCTR
0000 564 .IFF
0000 565 CMESC_'SERVICE = ALT_CHME
0000 566 .ENDC
0000 567 CHME #SERVICE
0000 568 .IF NOT BLANK EFN
0000 569 PUSHL #EFN
0000 570 PUSHL #IOSB
0000 571 JMP @EXESLDB_SYNCH
0000 572 .IFF
0000 573 RET
0000 574 .ENDC
0000 575 RET
0000 576 .IF BLANK ALT_CHME
0000 577 SERVICE = PREFIX'ECASCTR
0000 578 PREFIX'ECASCTR = PREFIX'ECASCTR + 1
0000 579 .IFF
0000 580 SERVICE = ALT_CHME
0000 581 .ENDC
0000 582 .ENDM LVEC_E
0000 583
0000 584
0000 585 LVEC_ALL - Mode of caller Loadable System Service Vector
0000 586
0000 587 LVEC_ALL PREFIX,SERVICE,EFN,IOSB
0000 588
0000 589 .MACRO LVEC_ALL,PREFIX,SERVICE,EFN,IOSB,ALT_CHMK
0000 590 JMP @EXES'SERVICE
0000 591 .IF NOT BLANK EFN
0000 592 ERROR ; SYNCH NOT ALLOWED FOR ALL-MODE SERVICES
0000 593 .ENDC
0000 594 .ENDM LVEC_ALL
0000 595
0000 596
00000000 0000 598 ECASCTR=0
```



```

0000 1213      :
0000 1214      :
0000 1215      :
0000 1216      :
0000 1217      :
0000 1218      :
0000 1219      :
0000 1220      :
0000 1221      :
0000 1222      :
0000 1223      :
0000 1224      :
0000 1225      :
0000 1226      :
0000 1227      :
0000 1228      :
0000 1229      :
0000 1230      :
0000 1231      :
0000 1232      :
0000 1233      :
0000 1234      :
0000 1235      :
0000 1236      :
0000 1237      :
0000 1238      :
0000 1239      :
0000 1240      :
0000 1241      :
0000 1242      :
0000 1243      :
0000 1244      :
0000 1245      :
0000 1246      :
0000 1247      :
0000 1248      :
0000 1249      :
0000 1250      :
0000 1251      :
0000 1252      :
0000 1253      :
0000 1254      :
0000 1255      :
0000 1256      :
0000 1257      :
0000 1258      :
0000 1259      :
0000 1260      :
0000 1261      :
0000 1262      :
0000 1263      :
0000 1264      :
0000 1265      :
0000 1266      :
0000 1267      :
0000 1268      :
0000 1269      :

```

DEFINE REMAINING SERVICES		
GSYSSRV	ADJSTK,K,3,-	:ADJUST OUTER MODE STACK POINTER
	<R2,R3,R4,R5,R6>,-	:REGISTERS R2-R6
	EXC MASK	:EXCEPTION MASK
GSYSSRV	ADJWSL,K,2,-	:ADJUST WORKING SET LIMIT
	<R2,R3,R4,R5>	:REGISTERS R2-R5
GSYSSRV	ALCDNP,K,4,-	:ALLOCATE DIAGNOSTIC PAGE
	<R2,R3,R4,R5,R6,R7>	:REGISTERS R2-R7
GSYSSRV	ALLOC,K,4,-	:ALLOCATE DEVICE
	<R2,R3,R4,R5,R6>	:REGISTERS R2-R6
GSYSSRV	ASCEFC,K,4,-	:ASSOCIATE COMMON EVENT FLAG CLUSTER
	<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>	:REGISTERS R2-R11
GSYSSRV	ACFIM,ALL,3,-	:CONVERT TO ASCII TIME
	<R2,R3,R4,R5,R6>	:REGISTERS R2-R6
GSYSSRV	ASSIGN,K,4,-	:ASSIGN I/O CHANNEL
	<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>	:REGISTERS R2-R11
GSYSSRV	BINTIM,ALL,2,-	:CONVERT TO BINARY TIME
	<R2,R3,R4,R5,R6,R7,R8>	:REGISTERS R2-R8
GSYSSRV	CANCEL,K,1,-	:CANCEL I/O ON CHANNEL
	<R2,R3,R4,R5,R6,R7,R8>	:REGISTERS R2-R8
GSYSSRV	CANTIM,K,2,-	:CANCEL TIMER REQUEST
	<R2,R3,R4,R5>	:REGISTERS R2-R5
GSYSSRV	CANWAK,K,2,-	:CANCEL WAKE UP REQUESTS
	<R2,R3,R4,R5>	:REGISTERS R2-R5
GSYSSRV	CRMPSC,K,12,-	:CREATE AND MAP SECTION
	<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>	:REGISTERS R2-R11
GSYSSRV	CLRPAR,K,2,-	:CLEAR HARD PARITY ERROR
	<R2,R3,R4,R5>	:REGISTERS R2-R5
GSYSSRV	CMEEXEC,E,2,-	:CHANGE MODE TO EXECUTIVE
	<R4>	:REGISTER R4
GSYSSRV	CMKRNL,K,2,-	:CHANGE MODE TO KERNEL
	<R4>	:REGISTER R4
GSYSSRV	CLREF,K,1,-	:CLEAR EVENT FLAG
	<R2,R3,R4,R5>	:REGISTERS R2-R5. SEE WAITFR COMMENTS.
GSYSSRV	CNTREG,K,4,-	:CONTRACT REGION
	<R2,R3,R4,R5,R6,R7>	:REGISTERS R2-R7
GSYSSRV	GETPTI,K,5,-	:GET PAGE TABLE INFORMATION
	<R2,R3,R4,R5,R6,R7,R8,R9,R10>	:REGISTERS R2-R10
GSYSSRV	CRELOG,ALL,4,-	:CREATE LOGICAL NAME
	<R2,R3,R4,R5,R6,R7,R8>	:REGISTERS R2-R8
GSYSSRV	CREMBX,K,1,-	:CREATE MAILBOX
	<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>	:REGISTERS R2-R11
GSYSSRV	CREPRC,K,12,-	:CREATE PROCESS
	<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>	:REGISTERS R2-R11
GSYSSRV	CREIVA,K,3,-	:CREATE VIRTUAL ADDRESS
	<R2,R3,R4,R5,R6,R7,R8>,-	:REGISTERS R2-R8
	EXC MASK	:EXCEPTION MASK
GSYSSRV	DACEFC,K,1,-	:DISASSOCIATE EVENT FLAG CLUSTER
	<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>	:REGISTERS R2-R11
GSYSSRV	DALLOC,K,2,-	:DEALLOCATE DEVICE
	<R2,R3,R4,R5,R8>	:REGISTERS R2-R5,R8
GSYSSRV	DASSGN,K,1,-	:DEASSIGN I/O CHANNEL
	<R2,R3,R4,R5,R6,R7,R8>	:REGISTERS R2-R8
GSYSSRV	DCLAST,K,3,-	:DECLARE AST SYSTEM SERVICE

[illegible]

```
0000 1270      <R2,R3,R4,R5>      :REGISTERS R2-R5
0000 1271      GSYSSRV DCL EXH,K,1,- :DECLARE EXIT HANDLER
0000 1272      <R2,R3,R4>      :REGISTERS R2-R4
0000 1273      GSYSSRV DEL LOG,ALL,3,- :DELETE LOGICAL NAME
0000 1274      <R2,R3,R4,R5,R6,R7,R8> :REGISTERS R2-R8
0000 1275      GSYSSRV DEL MBX,K,1,- :DELETE MAILBOX
0000 1276      <R2,R3,R4,R5>      :REGISTERS R2-R5
0000 1277      GSYSSRV DEL PRC,K,2,- :DELETE PROCESS
0000 1278      <R2,R3,R4,R5,R6,R7> :REGISTERS R2-R5
0000 1279      GSYSSRV DEL fVA,K,3,- :DELETE VIRTUAL ADDRESS
0000 1280      <R2,R3,R4,R5,R6,R7>,- :REGISTERS R2-R7
0000 1281      EXC MASK      :EXCEPTION MASK
0000 1282      GSYSSRV DGB LSC,K,3,- :DELETE GLOBAL SECTION
0000 1283      <R2,R3,R4,R5,R6,R7,R8,R9,R10> :REGISTERS R2-R10
0000 1284      GSYSSRV DLCDNP,K,2,- :DEALLOCATE DIAGNOSTIC PAGE
0000 1285      <R2,R3,R4,R5,R6,R7> :REGISTERS R2-R7
0000 1286      GSYSSRV DLCEFC,K,1,- :DELETE COMMON EVENT CLUSTER
0000 1287      <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> :REGISTERS R2-R11
0000 1288      GSYSSRV UPD SEC,K,8,- :UPDATE SECTION FILE
0000 1289      <R2,R3,R4,R5,R6,R7,R8> :R2-R8
0000 1290      GSYSSRV SND ERR,K,1,- :SEND MSG TO ERROR LOGGER
0000 1291      <R2,R3,R4,R5>      :REGISTERS R2-R5
0000 1292      GSYSSRV EXIT,K,1,- :IMAGE EXIT
0000 1293      <R4>,0      :REGISTER R4, ALWAYS ALLOWED!
0000 1294      GSYSSRV EXP REG,K,4,- :EXPAND PROGRAM REGION
0000 1295      <R2,R3,R4,R5,R6,R7,R8> :REGISTERS R2-R8
0000 1296      GSYSSRV FAO,ALL,0,- :FORMAT ASCII OUTPUT
0000 1297      <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> :REGISTERS R2-R11
0000 1298      GSYSSRV FAOL,ALL,0,- :FORMAT ASCII OUTPUT WITH VALUE LIST
0000 1299      <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> :REGISTERS R2-R11
0000 1300      GSYSSRV FORC EX,K,3,- :FORCE EXIT
0000 1301      <R2,R3,R4,R5>      :REGISTERS R2-R5
0000 1302      GSYSSRV IMG STA,ALL,6,- :IMAGE STARTUP
0000 1303      <>      :REGISTERS NONE
0000 1304      GSYSSRV SND JBC,E,7,- :SEND TO JOB CONTROLLER
0000 1305      <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> :REGISTERS R2-R11
0000 1306      GSYSSRV GET TIM,E,1,- :GET TIME
0000 1307      <>      :NO REGISTERS
0000 1308      GCOMPSRVB UPD SECW,- :UPDATE SECTION AND WAIT
0000 1309      <UPD SEC_MASK ! GET JPI_SYNCH_MASK>
0000 1317      GCOMPSRVE 1
0000 1318      GSYSSRV HIBER,K,0,- :HIBERNATE
0000 1319      <R2,R3,R4,R5>      :REGISTERS R2-R5
0000 1320      GSYSSRV IMG ACT,E,8,- :IMAGE ACTIVATION
0000 1321      <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> :REGISTERS R2-R11
0000 1322      GSYSSRV LCK PAG,K,3,- :LOCK PAGE IN MEMORY
0000 1323      <R2,R3,R4,R5,R6,R7,R8> :REGISTERS R2-R8
0000 1324      GSYSSRV LKW SET,K,3,- :LOCK PAGES IN WORKING SET
0000 1325      <R2,R3,R4,R5,R6,R7,R8> :REGISTERS R2-R8
0000 1326      GSYSSRV MGB LSC,K,7,- :MAP GLOBAL SECTION
0000 1327      <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> :REGISTERS R2-R11
0000 1328      GSYSSRV PURG WS,K,1,- :PURGE WORKING SET
0000 1329      <R2,R3,R4,R5,R6,R7,R8> :R2-R8
0000 1330      GSYSSRV NUM TIM,E,2,- :CONVERT TIME TO NUMERIC
0000 1331      <R2,R3,R4,R5,R6,R7> :REGISTERS R2-R7
0000 1332      GSYSSRV SND OPR,E,2,- :SEND MSG TO OPERATOR
0000 1333      <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> :REGISTERS R2-R11
```



```
0000 1334 GSYSSRV QIO,K,12,- :QUEUE I/O REQUEST
0000 1335 <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> :REGISTERS R2-R11
0000 1336 GSYSSRV READDEF,K,2,- :READ EVENT FLAG
0000 1337 <R2,R3,R4,R5> :REGISTERS R2-R5
0000 1338 GSYSSRV RESUME,K,2,- :RESUME PROCESS
0000 1339 <R2,R3,R4,R5> :REGISTERS R2-R5
0000 1340 GSYSSRV RUNDWN,K,1,- :RUNDOWN
0000 1341 <R2,R3,R4,R5,R6,R7> :REGISTERS R2-R7
0000 1342 GSYSSRV SND$MB,E,2,- :SEND MSG TO SYMBIONT MANAGER
0000 1343 <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> :REGISTERS R2-R11
0000 1344 GSYSSRV SCHDWK,K,4,- :SCHEDULE WAKEUP
0000 1345 <R2,R3,R4,R5,R6,R7,R8,R9> :REGISTERS R2-R9
0000 1346 GSYSSRV SETAST,K,1,- :SET AST ENABLE SERVICE
0000 1347 <R2,R3,R4,R5> :REGISTERS R2-R5
0000 1348 GSYSSRV SETEF,K,1,- :SET EVENT FLAG
0000 1349 <R2,R3,R4,R5> :REGISTERS R2-R5. SEE WAITFR COMMENTS.
0000 1350 GSYSSRV SETEXV,K,4,- :SET EXCEPTION VECTOR
0000 1351 <R2,R3,R4,R5> :REGISTERS R2-R5
0000 1352 GSYSSRV SETPRN,K,1,- :SET PROCESS NAME
0000 1353 <R2,R3,R4,R5,R6,R7,R8,R9> :REGISTERS R2-R9
0000 1354 GSYSSRV SETPRA,K,2,- :SET POWER RECOVERY AST
0000 1355 <R2,R3,R4,R5> :REGISTERS R2-R5
0000 1356 GSYSSRV SETIMR,K,4,- :SET TIMER
0000 1357 <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> :REGISTERS R2-R11
0000 1358 GSYSSRV SETPRI,K,4,- :SET PROCESS PRIORITY
0000 1359 <R2,R3,R4,R5> :REGISTERS R2-R5
0000 1360 GSYSSRV SETPRT,K,5,- :SET PAGE PROTECTION
0000 1361 <R2,R3,R4,R5,R6,R7,R8,R9> :REGISTERS R2-R9
0000 1362 GSYSSRV SETRWM,K,1,- :SET RESOURCE WAIT MODE
0000 1363 <R4> :REGISTER R4
0000 1364 GSYSSRV SETSFH,K,1,- :SET SYSTEM SERVICE FAILURE MODE
0000 1365 <R4>,EXC_MASK :REGISTER R4, AND EXECPTION MASK
0000 1366 GSYSSRV SETSWH,K,1,- :SET PROCESS SWAP MODE
0000 1367 <R4> :REGISTER R4
0000 1368 GSYSSRV SUSPND,K,2,- :SUSPEND PROCESS
0000 1369 <R2,R3,R4,R5> :REGISTERS R2-R5
0000 1370 GSYSSRV TRNLOG,ALL,6,- :TRANSLATE LOGICAL NAME
0000 1371 <R2,R3,R4,R5,R6,R7,R8> :REGISTERS R2-R8
0000 1372 GSYSSRV ULKPAG,K,3,- :UNLOCK PAGE FROM MEMORY
0000 1373 <R2,R3,R4,R5,R6,R7,R8> :REGISTERS R2-R8
0000 1374 GSYSSRV ULWSET,K,3,- :UNLOCK PAGES FROM WORKING SET
0000 1375 <R2,R3,R4,R5,R6,R7,R8> :REGISTERS R2-R8
0000 1376 GSYSSRV UNWIND,ALL,2,- :UNWIND PROCEDURE CALL STACK
0000 1377 <R2,R3,R4,R5> :REGISTERS R2-R5
0000 1378 GSYSSRV WAITFR,K,1,- :WAIT FOR EVENT FLAG
0000 1379 <R2,R3,R4,R5,R6> :REGISTERS R2-R6. IF R8 IS EVER USED
0000 1380 :THE RMS SYNCHRONIZATION CODE MUST BE
0000 1381 :MODIFIED TO SAVE IT ALSO.
0000 1382 GSYSSRV WAKE,K,2,- :WAKE PROCESS
0000 1383 <R2,R3,R4,R5> :REGISTERS R2-R5
0000 1384 GSYSSRV WFLAND,K,2,- :WAIT FOR LOGICAL AND OF EVENT FLAGS
0000 1385 <R2,R3,R4,R5,R6> :REGISTERS R2-R6
0000 1386 GSYSSRV WFLOR,K,2,- :WAIT FOR LOGICAL OR OF EVENT FLAGS
0000 1387 <R2,R3,R4,R5,R6> :REGISTERS R2-R5
0000 1388 GSYSSRV BRDCST,ALL,2,- :BROADCAST TO TERMINALS
0000 1389 <R2,R3,R4,R5,R6> :REGISTERS R2-R6
0000 1390 GSYSSRV DCLCMH,K,3,- :DECLARE CHANGE MODE HANDLER
```

0000	1391		<R4>	:SAVE R4
0000	1392	GSYSSRV	SETPFM,K,4,-	:SET PAGE FAULT MONITORING
0000	1393		<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>	:REGISTERS R2-R11
0000	1394	GSYSSRV	GETMSG,ALL,5,-	:GET MESSAGE
0000	1395		<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>	:REGISTERS R2-R11
0000	1396	GSYSSRV	DERLMB,K,1,-	:DECLARE ERROR LOG MAILBOX
0000	1397		<R2,R3,R4,R5>	:REGISTERS R2-R5
0000	1398	GSYSSRV	CANEXH,K,1,-	:CANCEL EXIT HANDLER
0000	1399		<R2,R3,R4,R5>	:REGISTERS R2-R5
0000	1400	GSYSSRV	GETCHN,K,5,-	:GET CHANNEL INFORMATION
0000	1401		<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>	:REGISTERS R2-R11
0000	1402	GSYSSRV	GETDEV,K,5,-	:GET DEVICE INFORMATION
0000	1403		<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>	:REGISTERS R2-R11
0000	1404	GSYSSRV	GETJPI,K,7,-	:GET JOB PROCESS INFORMATION
0000	1405		<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>	:REGISTERS R2-R11
0000	1406	GSYSSRV	PUTMSG,ALL,3,-	:PUT FORMATTED ERROR MESSAGE
0000	1407		<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>	:REGISTERS R2-R11
0000	1408	GSYSSRV	EXCMMSG,ALL,2,-	:OUTPUT EXCEPTION SUMMARY MESSAGE
0000	1409		<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>	:REGISTERS R2-R11
0000	1410	GSYSSRV	SNDACC,E,2,-	:SEND MSG TO ACCOUNTING MANAGER
0000	1411		<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>	:REGISTERS R2-R11
0000	1412	GSYSSRV	SETIME,K,1,-	:SET SYSTEM TIME
0000	1413		<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>	:REGISTERS R2-R11
0000	1414	GSYSSRV	SETPRV,K,4,-	:SET PRIVILEGES
0000	1415		<R2,R3,R4,R5,R6,R7,R8>	:REGISTERS R2-R8

0000 1417 :
0000 1418 :
0000 1419 :
0000 1420 :
0000 1421 :
0000 1422 :
0000 1423 :
0000 1424 :
0000 1425 :
0000 1471 :
0000 1472 :
0000 1473 :
0000 1474 :
0000 1475 :
0000 1476 :

SPECIAL VECTORS FOR AST DELIVERY AND CLEARING

SYSSCLRAST CLEARS THE CURRENTLY ACTIVE AST STATUS

SYSSGL ASTRET CONTAINS THE VALUE OF THE RETURN ADDRESS FROM
THE CALL INSTRUCTION USED TO DISPATCH AN AST. THIS VALUE CAN
BE USED WHEN SEARCHING UP THE STACK FOR THE AST CALL FRAME.

NOTE THAT THE CODE IN PSECT \$\$\$000 AT THIS POINT CANNOT EXCEED 320 (HEX)
WITHOUT MODIFYING THE RMS SYNCHRONIZATION CODE WHICH PRECEDES THE RMS
VECTORS WHICH CANNOT BE MOVED.


```
0000 1478 :
0000 1479 : Set up the base for the RMS service codes. We leave a hole so that
0000 1480 : other exec mode system services can be defined later in this module.
0000 1481 : The hole is defined by the offset between ECASCTR and RCASCTR; it
0000 1482 : is checked with an ASSUME at the end of all service definitions.
0000 1483 :
00000012 0000 1485 RCASCTR=ECASCTR+10
0000 1487 :
0000 1489 :
0000 1490 : CASE DISPATCHER FOR RMS SERVICES
0000 1491 :
0000 1492 : RO HAS SERVICE DISPATCH CODE.
0000 1493 : IF IN RANGE DISPATCHES TO APPROPRIATE RMS SERVICE,
0000 1494 : ELSE SIMPLY DOES AN RSB
0000 1495 :
0000 1496 .PSECT $$$RMSVEC,BYTE,NOVRT ;MUST BE FIRST PSECT IN RMS
22' 12' 50 AF 0000 1497 RMSSDISPATCH: ;MUST BE FIRST CODE IN FIRST RMS PSECT
0004 1498 CASEW RO,S^#RCASMIN,S^#RCASMAX
0004 1499
00000012 0004 1500 RCASE:
0004 1503 RCASMIN=RCASCTR
0004 1629 :
0004 1630 : HIGH USE RECORD OPERATIONS
0004 1631 :
0004 1632 RMSSRV DELETE ;DELETE A RECORD
0006 1633 .NLIST CND
0006 1634 RMSSRV FIND ;FIND RECORD
0008 1635 RMSSRV FREE ;RELEASE LOCK ON ALL RECORDS
000A 1636 RMSSRV GET ;GET A RECORD
000C 1637 RMSSRV PUT ;PUT A RECORD
000E 1638 RMSSRV READ ;READ A BLOCK
0010 1639 RMSSRV RELEASE ;RELEASE LOCK ON NAMED RECORD
0012 1640 RMSSRV UPDATE ;REWRITE EXISTING RECORD
0014 1646 RMSSRV WAIT ;STALL FOR RECORD OPERATION COMPLETE
0016 1652 RMSSRV WRITE ;WRITE BLOCK
0018 1653 :
0018 1654 : LOWER USAGE OPERATIONS
0018 1655 :
0018 1656 RMSSRV CLOSE ;CLOSE FILE
001A 1657 RMSSRV CONNECT ;CONNECT RAB
001C 1658 RMSSRV CREATE ;CREATE FILE
001E 1659 RMSSRV DISCONNECT ;DISCONNECT RAB
0020 1660 RMSSRV DISPLAY ;DISPLAY FILE INFORMATION
0022 1661 RMSSRV ERASE ;ERASE (DELETE) FILE
0024 1662 RMSSRV EXTEND ;EXTEND FILE ALLOCATION
0026 1663 RMSSRV FLUSH ;FINISH I/O ACTIVITY FOR STREAM
0028 1664 RMSSRV MODIFY ;MODIFY FILE ATTRIBUTES
002A 1665 RMSSRV NXTVOL ;NEXT VOLUME
002C 1666 RMSSRV OPEN ;OPEN FILE
002E 1667 RMSSRV REWIND ;REWIND FILE
0030 1668 RMSSRV SPACE ;POSITION FOR TRANSFER
0032 1669 RMSSRV TRUNCATE ;TRUNCATE FILE
0034 1670 RMSSRV ENTER ;ENTER FILENAME INTO DIRECTORY
0036 1671 RMSSRV PARSE ;PARSE FILENAME SPECIFICATION
0038 1672 RMSSRV REMOVE ;REMOVE FILENAME FROM DIRECTORY
003A 1673 RMSSRV RENAME,NARG=4 ;RENAME A FILE
003C 1674 RMSSRV SEARCH ;SEARCH A FILE DIRECTORY
```

```
003E 1675      RMSSRV SETDDIR,NARG=3,NOSYNC=1
0040 1676      ;SET DEFAULT DIRECTORY STRING
0040 1677      RMSSRV SETDFPROT,REGS=<R2,R3>,NARG=2,NOSYNC=1
0042 1678      ;SET DEFAULT FILE PROTECTION MASK
0042 1679      RMSSRV SSVEXC,REGS=<>,NOSYNC=1
0044 1680      ;GENERATE SYS SERV EXCEPTION
0044 1681      RMSSRV RMSRUNDWN,NARG=2,NOSYNC=1
0046 1682      ;PERFORM RUNDOWN ON RMS FILES
0046 1683      RMSSRV RMSRUHNDLR,NARG=5,NOSYNC=1
0048 1684      ;RMS Recovery Unit Handler
0048 1685      RMSSRV FILESCAN,NARG=3,NOSYNC=1
004A 1686      ;Perform syntax check for file specs
004A 1687      :
004A 1688      : ADD NEW RMS SERVICES IN FRONT OF THIS CODE!
004A 1689      :
004A 1690      : Now we add special non-vector code. Because of the CASE instruction
004A 1691      : used at the front of RMS, this code (and any future additional code)
004A 1692      : must be the last element of the RMS area.
004A 1693      :
004A 1694      :
004A 1695      GCOMPSRVB      ;Helper branch to error processing
004A 1704      GCOMPSRVE      1
004A 1705
004A 1732
```

```
.SBTTL REGION 2 OF SYS. SERV. VECTOR DEFINITIONS

004A 1734
004A 1735
004A 1736
004A 1737
004A 1738
004A 1739
004A 1740
004A 1741
004A 1742
004A 1743
004A 1744
004A 1745
004A 1746
004A 1747
004A 1748
004A 1762
004A 1763
004A 1764
004A 1765
004A 1766
004A 1767
004A 1768
004A 1769
004A 1770
004A 1771
004A 1772
004A 1773
004A 1774
004A 1775
004A 1776
004A 1777
004A 1786
004A 1787
004A 1788
004A 1798
004A 1799
004A 1800
004A 1809
004A 1810
004A 1811
004A 1820
004A 1821
004A 1822
004A 1861
004A 1862
004A 1863
004A 1864
004A 1865
004A 1866
004A 1867
004A 1868
004A 1869
004A 1870
004A 1871
004A 1872
004A 1873
004A 1874

Note: Service codes for exec mode services in this region are
reserved by the offset defined above between RCASCTR and ECASCTR.
If the ASSUME at the end of this section breaks, the offset must
be increased.

GSYSSRV ENQ,K,11,- : ENQUEUE
<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> : REGISTERS R2-R11
GSYSSRV DEQ,K,4,- : DEQUEUE
<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> : REGISTERS R2-R11
GCOMPSRVB ENQW,- : ENQUEUE AND WAIT
<ENQ_MASK ! WAITFR_MASK ! CLREF_MASK ! SETEF_MASK>
GCOMPSRVE 3 : RESERVE 3 QUADWORDS FOR VECTOR
GSYSSRV SETSSF,K,1,- : SET SYSTEM SERVICE FILTER MASK
<R4> : REGISTER R4
GSYSSRV SETSTK,K,3,- : SET STACK LIMITS
<R2,R3,R4> : REGISTERS R2,R3,R4
GSYSSRV GETSYI,K,7,- : GET SYSTEM INFORMATION
<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> : REGISTERS R2-R11
GSYSSRV IMGFIX,ALL,0,- : IMAGE ADDRESS RELOCATION FIXUP
<R2,R3,R4,R5> : REGISTERS R2-R5
GCOMPSRVB IMGFIX_2,- : ***** TEMP *****
<0>
GCOMPSRVE 1 : ***** TEMP *****
GSYSSRV GETDVI,K,8,- : GET DEVICE AND VOLUME INFORMATION
<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> : REGISTERS R2-R11
GCOMPSRVB GETDVIW,- : GET DEVICE INFORMATION AND WAIT
<GETDVI_MASK ! GETJPI_SYNCH_MASK>
GCOMPSRVE 1 :
GCOMPSRVB GETJPIW,- : GET JOB/PROCESS INFORMATION AND WAIT
<GETJPI_MASK ! GETJPI_SYNCH_MASK>
GCOMPSRVE 2 :
GCOMPSRVB GETSYIW,- : GET SYSTEM INFORMATION AND WAIT
<GETSYI_MASK ! GETJPI_SYNCH_MASK>
GCOMPSRVE 1 :
GCOMPSRVB SNDJBCW,- : SEND TO JOB CONTROLLER AND WAIT
<SNDJBC_MASK ! GETJPI_SYNCH_MASK>
GCOMPSRVE 1 :
GCOMPSRVB SYNCH,- : SYNCHRONIZE EFN AND IOSB
<WAITFR_MASK ! CLREF_MASK ! SETEF_MASK>
GCOMPSRVE 6 : RESERVE 6 QUADWORDS FOR VECTOR
GSYSSRV ERAPAT,K,3,- : GENERATE A SECURITY ERASE PATTERN
<R4> : SAVE R4
GSYSSRV CRELNT,K,8,- : CREATE LOGICAL NAME TABLE
<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> : REGISTERS R2-R11
GSYSSRV CRELNM,K,5,- : CREATE LOGICAL NAME
<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> : REGISTERS R2-R11
GSYSSRV DELLNM,K,3,- : DELETE LOGICAL NAME
<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> : REGISTERS R2-R11
GSYSSRV TRNLNM,K,5,- : TRANSLATE LOGICAL NAME
<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> : REGISTERS R2-R11
GSYSSRV GETLKI,K,7,- : GET LOCK INFORMATION
<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> : REGISTERS R2-R11
GCOMPSRVB GETLKIW,- : GET LOCK INFORMATION AND WAIT
```



```
004A 1875      <GETLKI_MASK ! WAITFR_MASK ! CLREF_MASK ! SETEF_MASK>
004A 1887      GCOMPSRVE 2 ; RESERVE 2 QUADWORDS FOR VECTOR
004A 1888
004A 1889      GSYSSRV ASCTOID,E,3,- ; ASCII TO IDENTIFIER CONVERSION
004A 1890      <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> ; REGISTERS R2-R11
004A 1891      GSYSSRV FINISH_RDB,E,1,- ; FINISH RDB CONTEXT STREAM
004A 1892      <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> ; REGISTERS R2-R11
004A 1893      GSYSSRV IDTOASC,E,6,- ; IDENTIFIER TO ASCII CONVERSION
004A 1894      <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> ; REGISTERS R2-R11
004A 1895      GSYSSRV BRKTHRU,K,11,- ; BREAK THROUGH WRITES
004A 1896      <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> ; REGISTERS R2-R11
004A 1897      GSYSSRV GRANTID,ALL,5,- ; GRANT IDENTIFIER TO PROCESS
004A 1898      <R2,R3> ; REGISTERS R2-R3
004A 1899      GSYSSRV REVOKID,ALL,5,- ; REVOKE IDENTIFIER FROM PROCESS
004A 1900      <R2,R3> ; REGISTERS R2-R3
004A 1901      GSYSSRV CHKPRO,K,1,- ; GENERAL PROTECTION CHECK ROUTINE
004A 1902      <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> ; REGISTERS R2-R11
004A 1903      GCOMPSRVB BRKTHRU,- ; BREAK THOUGH WRITE AND WAIT
004A 1904      <BRKTHRU_MASK ! GETJPI_SYNCH_MASK>
004A 1913      GCOMPSRVE 2
004A 1914      GSYSSRV GETQUI,E,7,- ; GET QUEUE INFORMATION
004A 1915      <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> ; REGISTERS R2-R11
004A 1916      GCOMPSRVB GETQUIW,- ; GET QUEUE INFORMATION AND WAIT
004A 1917      <GETQUI_MASK ! GETJPI_SYNCH_MASK>
004A 1926      GCOMPSRVE 2
004A 1927
00004028 004A 1928 ;
004A 1929 ;
004A 1930 ;
004A 1931      CJF$K$CASCTR = 16424
004A 1932      LDBSRV CJF$, ALLJDR, K, <R4>
004A 1933      LDBSRV CJF$, ASSJNL, K, <R4>
004A 1934      LDBSRV CJF$, CONUIC, K, <R4>
004A 1935      LDBSRV CJF$, CREJNL, K, <R4>
004A 1936      LDBSRV CJF$, DEALJDR, K, <R4>
004A 1937      LDBSRV CJF$, DEASJNL, ALL, <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>
004A 1938      LDBSRV CJF$, DEASJNL_INT, K, <R4>
004A 1939      LDBSRV CJF$, DELJNL, K, <R4>
004A 1940      LDBSRV CJF$, DMTJMD, K, <R4>
004A 1941      LDBSRV CJF$, DSPJNL, K, <R4>
004A 1942      LDBSRV CJF$, GETJNL, K, <R4>
004A 1943      LDBSRV CJF$, GETRUI, K, <R4>
004A 1944      LDBSRV CJF$, MODFLT, K, <R4>
004A 1945      LDBSRV CJF$, POSJNL, K, <R4>
004A 1946      LDBSRV CJF$, READJNL, K, <R4>
004A 1947      LDBSRV CJF$, RECOVER, K, <R4>
004A 1948      LDBSRV CJF$, MNTJMD, K, <R4>
004A 1949      LDBSRV CJF$, CRENWV, K, <R4>
004A 1950      LDBSRV CJF$, CONJNLF, K, <R4>
004A 1951      LDBSRV CJF$, DCNJNLF, K, <R4>
004A 1952      LDBSRV CJF$, FORCEJNL, ALL, <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>
004A 1953      LDBSRV CJF$, FORCEJNLW, ALL, <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>
004A 1954      LDBSRV CJF$, WRITEJNL, ALL, <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>
004A 1955      LDBSRV CJF$, WRITEJNLW, ALL, <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>
004A 1956      LDBSRV CJF$, GETCJI, K, <R4>
004A 1957      LDBSRV CJF$, DMTJMDW, K, <R4>, 4, 5, DMTJMD
004A 1958      LDBSRV CJF$, MODFLTW, K, <R4>, 4, 5, MODFLT
004A 1958      LDBSRV CJF$, POSJNLW, K, <R4>, 4, 5, POSJNL
```

```
00004010 004A 1959      LDBSRV CJF$, READJNLW,    K,  <R4>, 4, 5, READJNL
          004A 1960      LDBSRV CJF$, RECOVERW,    K,  <R4>, 5, 6, RECOVER
          004A 1961
          004A 1962 :
          004A 1963 :      RUF$KASCTR = 16400
          004A 1964 :
          004A 1965      LDBSRV RUF$, REENTERRU,    K,  <R2,R3,R4,R5,R6>
          004A 1966      LDBSRV RUF$, STARTRU,      K,  <R2,R3,R4,R5,R6>
          004A 1967      LDBSRV RUF$, PHASE1,        K,  <R2,R3,R4,R5,R6>
          004A 1968      LDBSRV RUF$, PHASE2,        K,  <R2,R3,R4,R5,R6>
          004A 1969      LDBSRV RUF$, CANCELRU,      K,  <R2,R3,R4,R5,R6>
          004A 1970      LDBSRV RUF$, MARKPOINTRU,   K,  <R2,R3,R4,R5,R6>
          004A 1971      LDBSRV RUF$, RESETRU,       K,  <R2,R3,R4,R5,R6>
          004A 1972      LDBSRV RUF$, DCLRUI,        K,  <R2,R3,R4,R5,R6>
          004A 1973      LDBSRV RUF$, CANRUH,        K,  <R2,R3,R4,R5,R6>
          004A 1974      LDBSRV RUF$, RUSTATUS,      K,  <R2,R3,R4,R5,R6>
          004A 1975 :
          004A 1976 :      End Recovery Unit consists of a two-phase commit, so we call each
          004A 1977 :      phase separately.
          004A 1978 :
          004A 1979      GCOMPSRVB ENDRU, <PHASE1_MASK ! PHASE2_MASK>, RUF$ ; End Recovery Unit
          004A 1990      GCOMPSRVE 2
          004A 1991      GSYSSRV MTACCESS,K,6,-      ;Mag tape installation specific access routi
          004A 1992      <R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> ;REGISTERS R2-R11
          004A 1993
          004A 1994 :
          004A 1995 :      End of system service vector definitions. New system services are
          004A 1996 :      to be added at this point.
          004A 1997 :
          004A 2000      ASSUME RCASMIN GE ECASCTR      ;Exec service codes must not collide with RM
          004A 2003
```

SYS&RMS_VECTOR
V04-000

- RMS SERVICE VECTOR DEFINITIONS L 1
REGION 2 OF SYS. SERV. VECTOR DEFINITION 16-SEP-1984 01:04:43 VAX/VMS Macro V04-00
5-SEP-1984 03:40:37 [SYS.SRC]CMODSSDSP.MAR;1

Page 22
(1)

```
00000022 004A 2273 RCASMAX=RCASCTR-<1+RCASMIN>
0000004A 2278 .PSECT $$$RMSVEC,BYTE,NOWRT
05 004A 2279 RSB ;NOT AN RMS EXEC MODE SERVICE
004B 2280 :
004B 2281 : SERVICE TO MERELY MOVE RMS STATUS CODE IN R2 TO R0 AND RET,
004B 2282 : THUS GENERATING A SYSTEM SERVICE FAILURE EXCEPTION IF ENABLED
004B 2283 :
00000049 004B 2284 RMS$$$SVEXC=-2
50 52 D0 004B 2285 MOVL R2,R0 ;MOVE STATUS CODE TO R0
04 004E 2286 RET ;AND LET RET DO THE REST
```


SYSSRMS_VECTOR
V04-000

- RMS SERVICE VECTOR DEFINITIONS M 1
REGION 2 OF SYS. SERV. VECTOR DEFINITION 16-SEP-1984 01:04:43 VAX/VMS Macro V04-00
5-SEP-1984 03:40:37 [SYS.SRC]CMODSSDSP.MAR;1
004F 2345 .END

Page 23
(2)

RSE
V04

SYSSRMS VECTOR
Symbol Table

- RMS SERVICE VECTOR DEFINITIONS

N 1

16-SEP-1984 01:04:43 VAX/VMS Macro V04-00
5-SEP-1984 03:40:37 [SYS.SRC]CMODSSDSP.MAR;1Page 24
(2)

```
$$ARGS = 00000008
$$T1 = 00000024
ASCTOID = 00000008
CATO = 00000001
CAT7 = 00000080
CJFSKASCTR = 00004028
CLOSE = 0000001C
CMEXEC = 00000000
CONNECT = 0000001D
CREATE = 0000001E
DEF_MASK = 00000081
DELETE = 00000012
DISCONNECT = 0000001F
DISPLAY = 00000020
ECASCTR = 0000000C
ENQS_ACMODE = 00000028
ENQS_ASTADR = 0000001C
ENQS_ASTPRM = 00000020
ENQS_BLKAST = 00000024
ENQS_EFN = 00000004
ENQS_FLAGS = 00000010
ENQS_LKMODE = 00000008
ENQS_LKSB = 0000000C
ENQS_NARGS = 0000000B
ENQS_PARID = 00000018
ENQS_PROT = 0000002C
ENQS_RESNAM = 00000014
ENTER = 0000002A
ERASE = 00000021
EXC_MASK = 00000080
EXTEND = 00000022
FILESCAN = 00000034
FIND = 00000013
FINISH_RDB = 00000009
FLUSH = 00000023
FREE = 00000014
GET = 00000015
GETDVIS_ASTADR = 00000018
GETDVIS_ASTPRM = 0000001C
GETDVIS_CHAN = 00000008
GETDVIS_DEVNAM = 0000000C
GETDVIS_EFN = 00000004
GETDVIS_IOSB = 00000014
GETDVIS_ITMLST = 00000010
GETDVIS_NARGS = 00000008
GETDVIS_NULLARG = 00000020
GETJPIS_ASTADR = 00000018
GETJPIS_ASTPRM = 0000001C
GETJPIS_EFN = 00000004
GETJPIS_IOSB = 00000014
GETJPIS_ITMLST = 00000010
GETJPIS_NARGS = 00000007
GETJPIS_PIDADR = 00000008
GETJPIS_PRCNAM = 0000000C
GETLKIS_ASTADR = 00000014
GETLKIS_ASTPRM = 00000018
GETLKIS_EFN = 00000004
```

```
GETLKIS_IOSB = 00000010
GETLKIS_ITMLST = 0000000C
GETLKIS_LKIDADR = 00000008
GETLKIS_NARGS = 00000007
GETLKIS_RESERVED = 0000001C
GETQUI = 0000000B
GETSYIS_ASTADR = 00000018
GETSYIS_ASTPRM = 0000001C
GETSYIS_CSIDADR = 00000008
GETSYIS_EFN = 00000004
GETSYIS_IOSB = 00000014
GETSYIS_ITMLST = 00000010
GETSYIS_NARGS = 00000007
GETSYIS_NODENAME = 0000000C
GETTIM = 00000002
IDTOASC = 0000000A
IMGACT = 00000003
MODIFY = 00000024
NUMTIM = 00000004
NXTVOL = 00000025
OPEN = 00000026
PARSE = 0000002B
PUT = 00000016
QIOS_ASTADR = 00000014
QIOS_ASTPRM = 00000018
QIOS_CHAN = 00000008
QIOS_EFN = 00000004
QIOS_FUNC = 0000000C
QIOS_IOSB = 00000010
QIOS_NARGS = 0000000C
QIOS_P1 = 0000001C
QIOS_P2 = 00000020
QIOS_P3 = 00000024
QIOS_P4 = 00000028
QIOS_P5 = 0000002C
QIOS_P6 = 00000030
RCASCTR = 00000035
RCASE = 00000004 R 02
RCASMAX = 00000022
RCASMIN = 00000012
READ = 00000017
RELEASE = 00000018
REMOVE = 0000002C
RENAME = 0000002D
REWIND = 00000027
RMSSCLOSE ***** X 02
RMSSCONNECT ***** X X 02
RMSSCREATE ***** X X 02
RMSSDELETE ***** X X 02
RMSSDISCONNECT ***** X X 02
RMSSDISPATCH 00000000 R X 02
RMSSDISPLAY ***** X 02
RMSSENTER ***** X X 02
RMSSERASE ***** X 02
RMSSEXTEND ***** X 02
RMSSFILESCAN ***** X 02
RMSSFIND ***** X 02
```

RSE
V04

SYSSRMS VECTOR
Symbol Table

- RMS SERVICE VECTOR DEFINITIONS B 2

16-SEP-1984 01:04:43 VAX/VMS Macro V04-00
5-SEP-1984 03:40:37 [SYS.SRC]CMODSSDSP.MAR;1Page 25
(2)

RMSSFLUSH	*****	X	02
RMSSFREE	*****	X	02
RMSSGET	*****	X	02
RMSSMODIFY	*****	X	02
RMSSNXTVOL	*****	X	02
RMSSOPEN	*****	X	02
RMSSPARSE	*****	X	02
RMSSPUT	*****	X	02
RMSSREAD	*****	X	02
RMSSRELEASE	*****	X	02
RMSSREMOVE	*****	X	02
RMSSRENAME	*****	X	02
RMSSREWIND	*****	X	02
RMSSRMSRUHNDLR	*****	X	02
RMSSRMSRUNDWN	*****	X	02
RMSSSEARCH	*****	X	02
RMSSSETDDIR	*****	X	02
RMSSSETDFPROT	*****	X	02
RMSSSPACE	*****	X	02
RMSSSSVEXC	= 00000049	R	02
RMSSSTRUNCATE	*****	X	02
RMSSUPDATE	*****	X	02
RMSSWAIT	*****	X	02
RMSSWRITE	*****	X	02
RMSRUHNDLR	= 00000033		
RMSRUNDWN	= 00000032		
RMSSWITCH	= 00000001		
RUF\$KASCTR	= 00004010		
SEARCH	= 0000002E		
SETDDIR	= 0000002F		
SETDFPROT	= 00000030		
SNDACC	= 00000007		
SNDJBC	= 00000001		
SNDJBC\$_ASTADR	= 00000018		
SNDJBC\$_ASTPRM	= 0000001C		
SNDJBC\$_EFN	= 00000004		
SNDJBC\$_FUNC	= 00000008		
SNDJBC\$_IOSB	= 00000014		
SNDJBC\$_ITMLST	= 00000010		
SNDJBC\$_NARGS	= 00000007		
SNDJBC\$_NULLARG	= 0000000C		
SNDOPR	= 00000005		
SND\$MB	= 00000006		
SPACE	= 00000028		
SSVEXC	= 00000031		
SYNCH\$_EFN	= 00000004		
SYNCH\$_IOSB	= 00000008		
SYNCH\$_NARGS	= 00000002		
TRUNCATE	= 00000029		
UPDATE	= 00000019		
UPDSECS\$_ACMODE	= 0000000C		
UPDSECS\$_ASTADR	= 0000001C		
UPDSECS\$_ASTPRM	= 00000020		
UPDSECS\$_EFN	= 00000014		
UPDSECS\$_INADR	= 00000004		
UPDSECS\$_IOSB	= 00000018		
UPDSECS\$_NARGS	= 00000008		

UPDSECS\$_RETADR	= 00000008
UPDSECS\$_UPDFLG	= 00000010
WAIT	= 0000001A
WRITE	= 0000001B

RSE
V04

+-----+
! Psect synopsis !
+-----+

PSECT name	Allocation	PSECT No.	Attributes
. ABS .	00000000 (0.)	00 (0.)	NOPIC USR CON ABS LCL NOSHR NOEXE NORD NOWRT NOVEC BYTE
\$AB\$\$	00000000 (0.)	01 (1.)	NOPIC USR CON ABS LCL NOSHR EXE RD WRT NOVEC BYTE
\$\$\$RMSVEC	0000004F (79.)	02 (2.)	NOPIC USR CON REL LCL NOSHR EXE RD NOWRT NOVEC BYTE

+-----+
! Performance indicators !
+-----+

Phase	Page faults	CPU Time	Elapsed Time
Initialization	30	00:00:00.08	00:00:00.94
Command processing	112	00:00:00.65	00:00:06.08
Pass 1	721	00:00:22.46	00:01:07.98
Symbol table sort	0	00:00:01.88	00:00:03.70
Pass 2	192	00:00:06.49	00:00:20.99
Symbol table output	21	00:00:00.17	00:00:00.61
Psect synopsis output	1	00:00:00.02	00:00:00.03
Cross-reference output	0	00:00:00.00	00:00:00.00
Assembler run totals	1079	00:00:31.76	00:01:40.35

The working set limit was 2100 pages.

252496 bytes (494 pages) of virtual memory were used to buffer the intermediate code.

There were 70 pages of symbol table space allocated to hold 1232 non-local and 0 local symbols.

2346 source lines were read in Pass 1, producing 15 object records in Pass 2.

44 pages of virtual memory were used to define 40 macros.

+-----+
! Macro library statistics !
+-----+

Macro library name	Macros defined
_\$255\$DUA28:[SYS.OBJ]LIB.MLB;1	6
-\$255\$DUA28:[SYS.LIB]STARLET.MLB;2	19
TOTALS (all libraries)	25

1210 GETS were required to define 25 macros.

There were no errors, warnings or information messages.

MACRO/LIS=LIS\$:RMSVECTOR/OBJ=OBJ\$:RMSVECTOR MSRC\$:RMSW/UPDATE=(ENH\$:RMSW)+MSRC\$:CMODSSDSP/UPDATE=(ENH\$:CMODSSDSP)+EXECML\$/LIB

0379 AH-BT13A-SE
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION
CONFIDENTIAL AND PROPRIETARY

0380 AH-BT13A-SE
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION
CONFIDENTIAL AND PROPRIETARY

SHELL
LIS

RSE
LIS

SCBVECTOR
LIS

SDAT
LIS

SHMSDRTN
LIS

SCSVEC
LIS

SCHED
LIS

SECADDT
LIS

SPTSKE
LIS

RUESVSUC
LIS